



Frank Bacon Machinery Sales Company, Inc.

4433 East Eight Mile Road • Warren, MI 48090-0886 • (586) 756-4280 • Fax (586) 756-8009 • Toll Free (800) 394-4280 •

e-mail: sales@frankbacon.com • On The Web: www.frankbacon.com

To:

Stock #: 11359-00

We offer for your consideration, subject to prior sale and conditions stated at the left for immediate acceptance.

Conditions of Sale	Description	Unit Price																				
<p>TERMS: 30% Deposit with the order, balance before shipment.</p> <p>We reserve the right to correct typographical errors.</p> <p>GUARANTEE: Unless otherwise specified, every machine is offered with the standard MDNA (MACHINERY DEALERS NATIONAL ASSOCIATION) Return privilege to ensure your complete satisfaction. If the machine is unsatisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable.</p> <p>Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.</p> <p>WARRANTY: FBMS Provides a ONE Year parts and labor Warranty on all reconditioned Testers and 90 Days on Reconditioned tools less all travel and/or Shipping Related Expenses. Unless otherwise specified.</p> <p style="text-align: center;">MDNA AMDA MMA ASTM SAE ASM</p>	<p>(1) USED 600,000 in-lb Capacity Tinius Olsen Electomatic Torsion Testing Machine updated with new SCR Variable Speed Servo Drive Controller. S/N 51126</p> <p style="text-align: center;"><u>SPECIFICATIONS:</u></p> <table style="width: 100%; border: none;"> <tr> <td style="width: 60%;">Torsion Capacity (<i>inch-pounds</i>).....</td> <td style="width: 40%;">600,000</td> </tr> <tr> <td>Test Speed (<i>degrees per minute</i>).....</td> <td>5° to 120° (<i>both directions</i>)</td> </tr> <tr> <td>Specimen: (<i>maximum diameter</i>).....</td> <td>5"</td> </tr> <tr> <td style="padding-left: 20px;">(<i>maximum length</i>).....</td> <td>10'</td> </tr> <tr> <td>Drive Motor: (<i>hp, rpm</i>).....</td> <td>30, 1750-2300</td> </tr> <tr> <td>Philadelphia Gear Reducer: (<i>gear size</i>).....</td> <td>875/1600</td> </tr> <tr> <td style="padding-left: 20px;">(<i>ratio</i>).....</td> <td>1600/1</td> </tr> <tr> <td>Approximate Overall Dimensions: (<i>WxDxH</i>).....</td> <td>23' 6" x 6' 9" x 5' 7"</td> </tr> <tr> <td>Approximate Weight.....</td> <td>18,500 lbs.</td> </tr> <tr> <td>Electrical Requirements: (<i>V,Hz,Ph</i>)</td> <td>460, 60, 3</td> </tr> </table> <p style="text-align: center;"><u>EQUIPPED WITH:</u></p> <ul style="list-style-type: none"> • An IBM Compatible P.C., Windows 7 Based Operating System with Monitor and Printer • MTWISTQuattro, Material Testing Software for Data Acquisition, Analysis, and Computer Controlled Testing • MTWISTQuattro, Micro console for sensor excitation and analog/digital signal processing. • Single directional grips <p style="text-align: center;">FOB Warren, MI Reconditioned and Guaranteed</p>	Torsion Capacity (<i>inch-pounds</i>).....	600,000	Test Speed (<i>degrees per minute</i>).....	5° to 120° (<i>both directions</i>)	Specimen: (<i>maximum diameter</i>).....	5"	(<i>maximum length</i>).....	10'	Drive Motor: (<i>hp, rpm</i>).....	30, 1750-2300	Philadelphia Gear Reducer: (<i>gear size</i>).....	875/1600	(<i>ratio</i>).....	1600/1	Approximate Overall Dimensions: (<i>WxDxH</i>).....	23' 6" x 6' 9" x 5' 7"	Approximate Weight.....	18,500 lbs.	Electrical Requirements: (<i>V,Hz,Ph</i>)	460, 60, 3	
Torsion Capacity (<i>inch-pounds</i>).....	600,000																					
Test Speed (<i>degrees per minute</i>).....	5° to 120° (<i>both directions</i>)																					
Specimen: (<i>maximum diameter</i>).....	5"																					
(<i>maximum length</i>).....	10'																					
Drive Motor: (<i>hp, rpm</i>).....	30, 1750-2300																					
Philadelphia Gear Reducer: (<i>gear size</i>).....	875/1600																					
(<i>ratio</i>).....	1600/1																					
Approximate Overall Dimensions: (<i>WxDxH</i>).....	23' 6" x 6' 9" x 5' 7"																					
Approximate Weight.....	18,500 lbs.																					
Electrical Requirements: (<i>V,Hz,Ph</i>)	460, 60, 3																					