



Frank Bacon Machinery Sales Company, Inc.

4433 East Eight Mile Road • Warren, MI 48090-0886 • (586) 756-4280 • Fax (586) 756-8009 • Toll Free (800) 394-4280 •

e-mail: sales@frankbacon.com • On The Web: www.frankbacon.com

To:

Stock #: 11275-00

We offer for your consideration, subject to prior sale and conditions stated at the left for immediate acceptance.

Conditions of Sale	Description	Unit Price
--------------------	-------------	------------

TERMS:
30% Deposit with the order, balance before shipment.

We reserve the right to correct typographical errors.

GUARANTEE:
Unless otherwise specified, every machine is offered with the standard **MDNA** (MACHINERY DEALERS NATIONAL ASSOCIATION) Return privilege to ensure your complete satisfaction. If the machine is unsatisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable.

Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.

WARRANTY:
FBMS Provides a ONE Year parts and labor Warranty on all reconditioned Testers and 90 Days on Reconditioned tools less all travel and/or Shipping Related Expenses. Unless otherwise specified.

(1) **USED MTS 1.1 KIP Capacity T-Slotted Bed Plate Mounted Fatigue Testing System.**

LOAD FRAME SPECIFICATIONS:

Model Number / Serial Number:	318.x
Capacity (KIP):	1
Number Of Columns:	2
Distance Between Columns:	21 "
Test Specimen Max. Length:	48"
Table Size (WxD):	4' x 6'
Approximate Overall Dimensions (WxDxH):	42" x 12" x 70"
Approximate Weight (Lbs):	900

EQUIPPED WITH:

- Crosshead Mounted MTS 1.1KIP, 3000 PSI Actuator, Model 242.01, SN 0131129, 6.0" Dynamic Stroke, LVDT & Area = 0.42 in sq
- MOOG Servo Valve, Model 760C-261A, 3000 PSI, SIG -50 to +50MA, SN 748
- MTS 1.1 KIP (5 Kn) Load Cell, Model 661.19E-01, SN 63472
- MTS 290 Hydraulic Service Manifold Model 290.14, SN 0132349 with Three MTS 111 3,000 psi Piston Accumulators: (2) One Pint Volume; (1) One Qt. Volume
- MTS Hydraulic Lifts and Hydraulic Locks with Controls
- MTS Frame Base with six (6) T-Nuts
- T-Slotted Table (WxDxH) : 4' x 6' x 6 5/8" w/(7)T-Slots (1 3/8" x 5/8"); Weight esti = 6,500 lbs
- Metal Stand Height 35.375"
- MTS Testline Control Counsel Equipped with: 410.81 Function Generator, SN 0112879; 407 Controller w/407.14 AC Conditioner, 407.12 DC Conditioner, 407.16 Valve Driver; 490.86 HSM Power Supply; 407.05 Pump Interface.
- MTS 1.5 GPM 3,000 PSI Hydraulic Power Supply, Model 506.00D, SN 0131945, 3HP Motor, 115/230V Amps 32/16, 60 Hz, 1 PH, Air/Oil Heat Exchanger. Hours 910

FOB Warren, MI

Cleaned & Serviced

MDNA | AMDA
MMA | ASTM | SAE
ASM