



# Frank Bacon Machinery Sales Company, Inc.

4433 East Eight Mile Road • Warren, MI 48090-0886 • (586) 756-4280 • Fax (586) 756-8009 • Toll Free (800) 394-4280  
e-mail: sales@frankbacon.com • On The Web: www.frankbacon.com

Stock #: 11317-01

We offer for your consideration, subject to prior sale and conditions stated at the left for immediate acceptance.

Conditions of Sale	Description	
--------------------	-------------	--

**TERMS:**  
30% Deposit with the order, balance before shipment.  
  
We reserve the right to correct typographical errors.  
  
**GUARANTEE:**  
Unless otherwise specified, every machine is offered with the standard **MDNA** (*MACHINERY DEALERS NATIONAL ASSOCIATION*) Return privilege to ensure your complete satisfaction. If the machine is unsatisfactory it may be returned to our warehouse, freight prepaid and in the original condition within 30 Days of shipment for a full refund less the cost of SPECIALIZED EQUIPMENT, NEW ITEMS AND RE-CERTIFICATION COSTS, When applicable.  
  
Care is taken to provide accurate specifications. However, Critical areas should be verified by Inspection.  
  
**WARRANTY:**  
**FBMS** Provides a ONE Year parts and labor Warranty on all reconditioned Testers and 90 Days on Reconditioned tools less all travel and/or Shipping Related Expenses. Unless otherwise specified.

(1) **USED Magnaflux, Model HMV-940 Duovec**, Multi-Directional, High Production Magnetic Particle Inspection Unit  
S/N 92124 Mfg. 1992

**SPECIFICATIONS:**

Magnetizing Intermittent Output Current(Amps): . . . . . 4000 HW DC  
  
Duty Cycle: . . . . . ½ Second On/5 Seconds Off  
Maximum Head Opening: . . . . . 22"  
Approximate Overall Dimensions(WxDxH): . . . . . 84" x 37" x 70"  
Approximate Weight(Lbs): . . . . . 2,500  
Electrical Requirements(V,Hz,Ph,A): . . . . . 460, 60, 3, 190 Line  
Air Requirements(PSI): . . . . . 80

**EQUIPPED WITH:**

- Two Infinitely-Adjustable, Self-Regulating Current Controls to Select Desired Magnetizing Current
- Adjustable Tailstock for Varying Part Lengths
- Three-Position Selector Switch (contacts, coils, duovec) for Versatile Operation
- Current Assurance Indicator for Quick, easy Verification that Current has Flowed
- Alarm and Light to Indicate Failure of Current Flow
- Digital Ammeters for Accurate (retained) Ampere Reading
- Footswitch to Control Clamping, Magnetizing Current and Part Release
- Push Bar to Activate Magnetizing Current for Initial Set Up
- Internal Power Pack
- Hand Held Hose for Manual Bath Application
- Rugged Construction and Stainless Steel Tank

**FOB Warren, MI**

**Reconditioned and Guaranteed**

MDNA | AMDA  
MMA | ASTM | SAE  
ASM